

VEO-AXS4P

HDMI 2.0 AUDIO EXTRACTOR

Supporting data rates up to 18Gbps



PRODUCT OVERVIEW

Ecler VEO-AXS4P is a professional HDMI audio extractor that allows to de-embed audio from a HDMI signal, including audio from 4K sources. VEO-AXS4P provides uncompressed LPCM analogue stereo signal through RCA and Phoenix balanced output as well as Dolby Digital and DTS multichannel signals through the coaxial S/PDIF digital output. VEO-AXS4P is HDCP 2.2 and HDMI 2.0 compliant, supporting data rates up to 18 Gbps and video resolutions up to 4K/60Hz with 4:4:4 chroma sample and HDR contents.

KEY FEATURES

- Audio EDID Settings: Auto/2.0 CH/5.1CH
- Extracts the digital HDMI audio signal from the HDMI input to 2 channel analog stereo output or to 5.1 S/PDIF output
- Signal amplification and equalization to extend HDMI input and output ports up to 10 meters (33 feet)
- Supports LPCM, Dolby Digital and DTS
- Supports resolution up to 4K@60Hz YUV4:4:4
- Supports deep color up to 36bit
- Supports samplerate up to 192 KHz and resolutions up to 24 bit
- HDCP2.2/1.4 Compliant
- Supports CEC

APPLICATIONS

 All the applications where HDMI audio de-embedding is required



TECHNICAL DATA

Audio and Video performances Supported Resolutions	Up to 4K2K@60Hz
Colorspace	RGB, YCbCr
Color depth	8-bit, 10-bit, 12-bit
Signal Bandwidth	18 Gbps
CEC	Pass Through
НДСР	2.2/1.4 Compliant
HDR	HDR10 Supported
Audio Formats	LPCM 2.0, LPCM 5.1, Dolby Digital, DTS-HD Master Audio, Dolby true-HD
Audio Bit Depth	Support of 24-bit
Sample Rate	32 KHz, 44.1 KHz, 48 KHz, 88.2 KHz, 96 KHz, 176.4 KHz, 192 KHz
HDMI Distance	up to 10 meters with Ecler VEO cables
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Humidity	10 to 90% non-condensing
Power Consumption	3 W Max
Power Supply	AC 100V ~ 240V 50/60Hz Output: DC 12V1A




MISCELLANEOUS

Dimensions L x W x H 129 x 21.5 x 77 mm (5.08" x 0.85" x 3.03")

Weight 244 g / 0.538 lb

MECHANICAL DIAGRAM











3/3