

HALO-4B150

AMPLIFIERS

Networkable Amplifiers



PRODUCT OVERVIEW

HALO-4B150 is a 4-channel Class D amplifier with networked DSP, delivering 4×150 W in low-impedance mode at 4Ω or 8Ω . Its four output channels can be bridged to drive high-impedance 70 V or 100 V loudspeaker lines.

It features 4 balanced analogue inputs, 4 Dante®/AES67 digital inputs and outputs, 2 balanced auxiliary outputs, and a flexible 4×6 digital matrix. Its comprehensive DSP includes input and output parametric equalization, graphic output equalization, crossovers, delay, and configurable peak and RMS limiters.

The built-in web application provides intuitive configuration, control and monitoring of the amplifier. Two Ethernet ports with integrated switch functionality allow network daisy-chaining and provide access to control, Dante®/AES67 audio transport and remote management. HALO-4B150 also supports customizable user control panels and integration with EclerCLOUD and the PULSO digital control panel series.

KEY FEATURES

- 4 amplified outputs
- 4 Dante®/AES67 outputs (2 flows) and 4 Dante®/AES67 inputs (2 flows).
- 4 analogue inputs.
- 2 Ethernet ports for Dante®/AES67 and Control management.
- MicroSD/SDHC audio player.
- Internal matrix and signal processing.
- Web application for device configuration.
- Event control and scheduling for automation.
- Customizable user panels.
- Remote control user app for iOS/Android/Web.
- Ultra-low power consumption mode.
- Compatible with the Remote Monitoring & Control Platform EclerCLOUD.

APPLICATIONS

- Retail
- Hospitality
- Education
- Corporate
- Sport & Wellness

ACCESSORIES & COMPATIBLE PRODUCTS

- PULSO Series



TECHNICAL SPECIFICATIONS

HALO-4B150

CHANNELS		
Number of Outputs channels	4	
Output connection type	2-pin Euroblock. Pitch: 7,62 mm	
Output configuration	4 Lo-Z connections, bridgeable for Hi-Z	
Number of Inputs channels	4	
Input connection type	3-pin Euroblock. Balanced. Pitch: 3,5 mm	
Number of digital inputs	4	
Input configuration	Digital matrix 4 in x 6 out	
AUXILIAR OUTPUTS		
Number of auxiliar outputs	2	
Auxiliar output connection type	3-pin Euroblock. Balanced. Pitch: 3,5 mm	
DIGITAL OUTPUTS		
Number of digital outputs	4	
Digital output connection type	Ethernet, managed via Dante®/AES67 Controller	
OUTPUT POWER All channels driven @1kHz @CF9dB @ 1%THD		
Max output power @ 8Ω	150 W	
Max output power @ 4Ω	150 W	
Max output power @ 8Ω bridge mode	300 W	
Max output power @ 100V	280 W	
Max output power @ 70V	300 W	
OUTPUT POWER Single channel driven @1kHz @CF9dB @ 1%THD		
Max output power @ 8Ω	150 W	
Max output power @ 4Ω	150 W	
Max output power @ 8Ω bridge mode	300 W	
Max output power @ 100V	280 W	
Max output power @ 70V	300 W	
OUTPUT POWER - All channels driven @ 1%THD		
Max output power @ 8Ω	150 W	
Max output power @ 4Ω	150 W	
Max output power @ 8Ω bridge mode	300 W	
Max output power @ 100V	280 W	
Max output power @ 70V	300 W	
OUTPUT POWER - Single channel driven		
Max output power @ 8Ω	150 W	
Max output power @ 4Ω	150 W	
Max output power @ 8Ω bridge mode	300 W	
Max output power @ 100V	280 W	
Max output power @ 70V	300 W	
SIGNAL		
Voltage gain	28 to 40 dBV 30,2 to 42,2 dBu	
Input sensitivity	0dBV to +12dBV	
Input impedance	>5kΩ Single Ended >10kΩ Differential Pair	

Max input level	+18 dBV +20,2 dBu
Frequency response	20Hz - 25kHz
THD + Noise	< 0,1 % 0,03 Typical @ 1kHz, from 0,1W to Full Power
SNR	>85 dB
Crosstalk	>80 dB
CMRR	>65 dB Typical
Damping factor	>500 @ 8Ω, from 20Hz to 1kHz
ELECTRICAL	
Power supply	Universal, regulated SMPS with PFC
AC mains requirement	100-240 V @ 50-60Hz (±10%)
Power factor correction	> 0,8 (Total Output Power > 150W)
AC mains connector	IEC C14 inlet
POWER CONSUMPTION	
Power Consumption (1/8 POWER, @ 4Ω all channels driven)	126 W 178 VA
Power Consumption (IDLE)	27 W 61 VA
Power Consumption (STBY/SLEEP)	12 W 33 VA
POWER & HEAT @230VAC	
1/4 POWER, @ 4Ω (all channels driven)	
Power	218 W 272 VA
Current Draw	1,2 Arms
Thermal Loss	232 BTU/h 59 kcal/h
1/8 POWER, @ 4Ω (all channels driven)	
Power	126 W 178 VA
Current Draw	0,8 Arms
Thermal Loss	174 BTU/h 44 kcal/h
IDLE (all channels driven)	
Power	27 W 61 VA
Current Draw	0,27 Arms
Thermal Loss	92 BTU/h 23 kcal/h
STANDBY/SLEEP MODE (all channels driven)	
Power	12 W 32 VA
Current Draw	0,14 Arms
Thermal Loss	41 BTU/h 10 kcal/h
POWER & HEAT @120VAC	
1/4 POWER, @ 4Ω (all channels driven)	
Power	220 W 236 VA

1/8 POWER, @ 4Ω (all channels driven)	Current Draw	1,9 Arms
	Thermal Loss	239 BTU/h 60 kcal/h
	Power	126 W 144 VA
IDLE (all channels driven)	Current Draw	1,2 Arms
	Thermal Loss	174 BTU/h 44 kcal/h
	Power	26 W 48 VA
STANDBY/SLEEP MODE (all channels driven)	Current Draw	0,2 Arms
	Thermal Loss	89 BTU/h 22 kcal/h
	Power	12 W 24 VA
	Current Draw	0,2 Arms
	Thermal Loss	41 BTU/h 10 kcal/h

TECHNOLOGIES

Amplification technology	Class D
Energy saving	Auto standby function programmable per channel Sleep Mode function selectable
Efficiency	68% (1/4 POWER, @ 4Ω, 230VAC IN)
Cooling	Fan
Maximum fan noise	49 dBA (Maximum acoustical noise @1m)

DSP

AD converters	32 Bit @ 48 kHz - AKM 111 dB Dynamic Range, -103 dB THD+N
DA converters	32 Bit @ 48 kHz - AKM 115 dB Dynamic Range, -107 dB THD+N
Sample rate converter	48 kHz
Internal precision	32 / 64 bit floating point
Latency	5,6 ms
Memory/Presets	20 presets
Delay	Up to 1s at outputs
Equalizer	Graphic EQ - 8 bands at Outputs Parametric EQ - 12 bands both Inputs and Outputs
Crossover	With Parametric EQ
Limiters	Output Peak and RMS Limiter, configurable by user
Inputs processing	PEQ
Outputs processing	PEQ, GEQ, Delay, Limiters

PROTECTIONS

DC protection	Yes
HF protection	Yes
Short-circuit protection	Yes
Clip limiter	Yes
Long term limiter	Yes
Thermal protection	Yes



REMOTE CONTROL CONNECTIONS		
ON / OFF	No	
GPIs	x4 GPIs (0-12V)	
External MUTE	Yes, contact	
LOCAL CONTROL		
Attenuators	Programmable Front panel knobs	
Output mode settings	Output mode selection per channel in Lo-Z modes: 4Ω, 8Ω. Output mode selection per pair of channels in Hi-Z modes (bridge): 100V, 70V, 8Ω BR	
RUN/SLEEP mode	Yes, front panel push-button	
Power ON/OFF	Yes, back panel switch	
SETTINGS		
Filters	20/35/50/70 Hz, high pass filter selectable per output Fixed 15Hz 3rd order Butterworth	
Output settings	Lo - Z 4Ω / 8Ω configurable each channel Hi - Z 8Ω / 70V / 100V configurable bridged pair	
Gain	28 to 40 dBV 30,2 to 42,2 dBu	
Auto standby function	Yes, configurable by user	
Auto standby threshold	-30dB to -80dB in -10dB steps	
Auto standby time	30s to 1h, configurable via steps	
Power ON/OFF	Yes, front panel switch	
CONNECTIVITY		
Ethernet	Ethernet Base-Tx 10/100/1000Mb Auto X-Over 2 Ports Ethernet Switch capability	
DANTE Protocol	Dante®/AES67 4x Tx / 4x Rx channels (2/2 flows)	
Programming and control	Embedded web application	
MONITORING		
Signal Present	SP/CLIP LED (Green - Orange - Red) per channel	
Clipping	SP/CLIP LED (Green - Orange - Red) per channel	
Protect	PROT LED (Red) per channel	
Standby / Mute	MUTE / STBY LED (Red, Orange) per channel	
Thermal	THERMAL LED (Orange) per channel	
Dante	DANTE LED (Green / red) per unit	
Data	DATA LED (White) per unit	
On	ON LED (Green) per unit	
DIGITAL ENGINE		
Processor	Quad core 64bits 1,5GHz	
AUDIO CONVERTERS		
Sampling rate	48 kHz	
Resolution	24 bit	
Dynamic range	111 dB	
REAL-TIME CLOCK		
Retention time	30 days	
Accuracy	1 minutes /month	
LOCAL STORAGE		
Micro SD	SDXC	
Capacity	Up to 2TB	
File system	FAT16, FAT 32, VFAT (read/write) NTFS (read) Multi-partition up to 1	

Playable audio files	mp3, ogg, WAV, FLAC, AIFF
Files analysis	65354 playable folders 65354 playable folders within each folder 65354 playable files within each folder
Folder hierarchy	Up to 8 containing the root directory
Sorting	UNICODE, in alphabetical order Up to 100 folders / files by folder Folders/files over 100 sorted in the FAT order
PHYSICAL	
Operating temperature	Min.: 0 °C / 32 °F Max.: 50 °C / 122 °F Performance may be reduced above 40 °C / 104 °F
Operating humidity	5 - 85% RH, non-condensing
Storage temperature	Min.: -10 °C / 14 °F Max.: 50 °C / 122 °F
Storage humidity	5 - 85% RH, non-condensing
Installation options	Rack 19" installation & desktop
Included accessories	Schuko AC cable, Euroblock Connectors (inputs /outputs), Desktop feet, rack 19" installation hardware
Optional accessories	Compatible with Ecler PULSO Series.
Dimensions (WxHxD)	Handles incl.: 482.5 x 44 x 405,6 mm. / 19 x 1.73 x 15.97 in. Handles excl.: 482.5 x 44 x 372 mm. / 19 x 1.73 x 14.65 in.
Weight	5.2 kg / 11.46 lb.
Shipping dimensions (WxHxD)	583 x 75 x 580 mm / 22.95 x 2.95 x 22.83 in.
Shipping weight	7.75 Kg / 17.09 lb.

MECHANICAL DIAGRAM



Ecler HALO-4BI50 Mechanical Diagram



All the measurements are in mm

6I-1234-0100

www.ecler.com



Motors, 166-168
08038 – Barcelona - Spain
www.ecler.com

All product characteristics are subject to variation due to production tolerances

NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.

For technical queries contact your supplier, distributor or complete the contact form on our website, in [Support / Technical requests](#).