

ARQIS208i+

LOUDSPEAKERS

High-Performance Loudspeakers





A&E SPECIFICATIONS

The loudspeaker shall be a 2-way wooden loudspeaker cabinet, incorporating 2 x 8" low-frequency woofers and a 1" rotatable high-frequency compression driver, designed for permanent installation where sound performance and architectural / interior design integration are required.

It shall have a continuous power handling of 400 W RMS (AES2), a program power handling of 800 W and a peak power handling of 1600 W, at a nominal impedance of 8 Ω. The recommended amplifier power shall be 800 W RMS, with a recommended high-pass protection filter at 67 Hz (minimum 12 dB/octave).

The effective frequency range (-10 dB) shall be from 67 Hz to 19 kHz, with the crossover filter at 2.6 kHz. The on-axis sensitivity shall be 93 dB when measuring with an input signal of 1 W at a distance of 1 m, while the maximum sound pressure level shall be 119 dB continuous and 125 dB peak. The coverage angle shall be 110° x 150° (H x V).

The enclosure shall be constructed out of MDF, with a steel grille secured by screw fixation, and shall be IP31 rated. It shall be available in white (RAL 9003) and black (RAL 9005). Connection shall be made via 1 x Euroblock and 1 x Speakon connector.

It shall include a "U" wall bracket allowing tilt adjustment. Surface, wall and desktop installation shall be possible, and the enclosure shall provide 4 x M6 and 12 x M8 flying points. The operating temperature range shall be from -20 °C to 70 °C.

The enclosure shall be 260 mm wide, 710 mm high and 290 mm deep, and the weight shall not exceed 20 kg.

The loudspeaker shall be the ECLER ARQIS208i+.

98-0030-0100

Motors, 166-168
08038 – Barcelona - Spain
www.ecler.com

All product characteristics are subject to variation due to production tolerances
NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.
For technical queries contact your supplier, distributor or complete the contact form on our website, in **Support / Technical requests.**